



## Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

### ET-FMP50

Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

#### Key Features

---

Flexible Design Streamlines Installation

---

Simple Yet High-Precision Adjustment

---

Smooth and Continuous Content Playback





## ET-FMP50

<https://oc.connect.panasonic.com/au/en/et-fmp50-series>

<b>Type</b>	Box-type
<b>Terminals   LAN</b>	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T, NDI® compatible
<b>Terminals   Audio Out</b>	3.5 mm stereo mini-jack
<b>Video Format</b>	HAP*2 / H.264, 8-bit, 3840 x 2160 pixels, 60p, YPBPR 4:2:0, 300 Mbps / H.265, 8-bit, 4096 x 4096 pixels, 60p, YPBPR 4:2:0, 300 Mbps
<b>Storage</b>	4 TB
<b>Operating System</b>	Linux®
<b>Power Supply</b>	AC 100–240 V, 50/60 Hz
<b>Dimensions (W x H x D)</b>	Approx. 210 mm x 44 mm x 295 mm (8 1/4" x 1 23/32" x 11 5/8") (Excluding feet)
<b>Weight</b>	Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord)
<b>Operating Environment</b>	Operating temperature: 0–40 °C (32–104 °F), operating humidity: 10–80 % (no condensation)
<b>Note</b>	*1 When four HDMI™ outputs are used simultaneously. *2 ET-FMP50 only. Available via a firmware update from CY2025 Q1. *3 For the ET-FMP20 (512 GB) and ET-SBFMP10 (512 GB), approximately 30 GB of the total storage space is allocated for system usage and is unavailable to the user. *4 The operating temperature range may differ according to the specific projector model paired with the ET-SBFMP10
	3840 x 2160/60p x 1 or 1920 x 1080/60p x 4*1
	AAC-LC, 16-bit, stereo
	64 W
	HDMI™ x 4, Audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz)