



Compact Remote Camera Controller

AW-RP60GJ

Equipped with a GUI menu screen for clear visibility and a joystick for intuitive control. Compact Remote Camera Controller with PoE* support for single cable connection.

Key Features

Equipped with a 3.5-type LCD screen

Flexible customization features

New Joystick with enhanced operability

PoE*1 support/Advanced camera adjustment

*1: PoE is the abbreviation for Power over Ethernet.



AW-RP60GJ

<https://oc.connect.panasonic.com/nz/en/products/broadcast-proav/aw-rp60gj>

Power Requirements	12 V DC (10.8 V to 13.2 V)
PoE*	IEEE802.3af standard: 42 V to 57 V DC (Camera Input)
Current Consumption	0.9 A (XLR connector input), 0.3 A (PoE power supply)
Mass	1.5 kg (3.31 lbs)
Dimensions (W x H x D) (mm)	W 210 mm x H 92 mm x D 177 mm (excluding protrusions)
Dimensions (W x H x D) (inch)	8-9/32 inches x 3-5/8 inches x 6-31/32 inches (excluding protrusions)
Display	3.5-type liquid crystal (QHD 960 x 540)
Connection Specifications	No. of Connectable Cameras :
	200 (IP), 5 (RS422)
	*Up to 100 for cameras other than the AW-UE150
	Remote Camera Selection :
	5 (6 to 200 controlled from the LCD)
	No. of Camera Groups :
	20 (10 units/group)
	No. of Memory Presets :
	100
Note	*PoE is the abbreviation for Power over Ethernet.