



Short-Throw Zoom Lens for 3-Chip DLP™ Projectors

ET-D3LEW200

The Zero Offset Ultra Short Throw Fixed-Focus Lens is designed for compatibility with RZ21 series, RZ31 series projectors.

Key Features

Minimize Throw Distance, Increase Flexibility

Wide-Range Adjustment After Projector Installation

Lens Design Delivers an Unobstructed View

ET-D3LEW200

<https://oc.connect.panasonic.com/nz/en/et-d3lew200>

| | |
|----------------------------------|--|
| Lens type | Short-Throw Zoom Lens |
| F Value | 2.5 |
| Focal Length | 13.8–18.1 mm (17/32"–23/32") |
| Screen Size | 200-600 inches |
| Throw ratio 4K+ | 0.693–0.913:1 |
| Throw ratio WUXGA | 0.645–0.850:1 |
| Throw ratio SXGA+ | 0.699–0.921:1 |
| Lens-shift*1 Vertical | ±59 % |
| Lens-shift*1 Horizontal | ±19 % |
| Zoom | Yes |
| Dimensions (W×H×D) | 250 × 193 × 495 mm (9 27/32" x 7 19/32" x 19 1/2") |
| Weight | Approx. 9.0 kg (19.8 lbs) |
| Compatible projectors | RQ32K/RZ31K Series/RQ22K/RZ21K Series |

Note * Value is for ceiling installations using the PT-RQ22K. Lens-shift value will vary by model. Please see the Throw Distance Calculator for more information: <https://panasonic.net/cns/projector/calculator/tdc/>. For floor installations, up and right shift will be defined as a positive value. Down and left shift will be defined as a negative value.