



## Simple plug & play collaboration solution

# **TY-WPS1** series

"PressIT" is Panasonic's Wireless Presentation System that allows easy screen collaboration with just a single press of a button. This elegant solution, designed to make collaboration quick and simple in meeting rooms, can connect up to 32 devices at one time, allowing users to present on screen or via a projector at the touch of a button..

#### **Key Features**

For video and audio signals from PCs, iOS/Android, and other mobile devices

Two types of receivers: Set top box compatible with all displays and projectors, SDM board for SQ1 and SQE1 displays

Compatible with HDMI-CEC command control, linked operation with CEC compatible devices

Up to 4 simultaneous display sources, and up to 32 Transmitter simultaneous connections

No need for software and driver installation or network connection

# Panasonic CONNECT



### TY-WPS1 series

https://oc.connect.panasonic.com/nz /en/pressit-wireless-presentationsystem







Product	Wireless Presentation System Basic Set
Max. output resolution / Framerate	Receiver: 1920 x 1080/60p,3840 x 2160/30p (max.)
Max. input resolution / Framerate	Transmitter: 1920 x 1080/60p (max.)
Number of simultaneous connections	32
Number of sources simultaneous on screen	4
Data Rate   Wired	10/100/1000 (Mbps)
Data Rate   Wireless	Receiver: 867 Mbps (max.)  Transmitter: 433 Mbps (max.)
Frequency Band	5 GHz (5180 MHz to 5240 MHz)
Wireless Communication Standard	Receiver : IEEE802.11/a/n/ac
	Transmitter: IEEE802.11ac
Security	WPA/WPA2 (AES)
Reach (Max distance between transmitter and receiver)	30 m (When the line of sight/wave conditions are good)
Connection terminal	Description of LIDAK (LICE A (ferred - VDIAF (LAN))
Connection terminal	Receiver : HDMI/USB-A (female)/RJ45 (LAN)
	Transmitter: HDMI/USB-A (female)/USB-A (male)
Power Requirements	Receiver: DC 5 V/2 A
	Transmitter: DC 5 V/0.9 A
Power consumption (During image	Receiver: 10 W
display)	Transmitter: 4.5 W
Temperature   Operating	Temperature: 0 °C to 35 °C (32 °F to 95 °F)
Temperature   Storage	Temperature: -20 °C to 60 °C (-4°F to 140°F)
Dimensions (W x H x D)	Receiver: 120 x 26 x 81 mm
	(4.71" x 1.03" x 3.19") ( Excluding antenna part )
	Transmitter: 50.8 x 19.5 x 73.2 mm
	(2.00" x 0.80" x 2.86") (Excluding cables)
	Case: 151.3 x 41.6 x 198.0 mm
	(5.96" x 1.64" x 7.8")
Weight	Receiver: Approx. 181 g / 0.4 lbs

Transmitter: Approx. 110 g / 0.3 lbs Case: Approx. 315 g / 0.7 lbs