



Conveniently Compact Switcher Achieves High-quality Video

AV-HSW10

IP Live Switcher with intuitive and compact design takes online communication one level higher.

Key Features

Diverse Interfaces to Suit Wide-ranging Needs

Diverse Keyers for More Attractive Video

Multiviewer With 10 Selectable Patterns

Remote Control With Software Control Panel



AV-HSW10

<https://oc.connect.panasonic.com/nz/en/av-hsw10>

| | |
|-------------------------------|--|
| Video Input | 3G-SDI |
| | Baseband mode: 4 or 3 |
| | IP mode: 1 |
| | HDMI |
| | Baseband mode: 1 or 2 |
| | IP mode: 1 |
| | NDI®*1*2/Streaming |
| | Baseband mode: 2 |
| | IP mode: 3 |
| | |
| Video Output | 3G-SDI |
| | Baseband mode: 2 |
| | IP mode: 2 |
| | HDMI |
| | Baseband mode: 1 |
| | IP mode: 2 |
| | NDI®*1*2/Streaming |
| | Baseband mode: 2 |
| | IP mode: 2 |
| | |
| Video Format | |
| | 3G-SDI |
| | 1080/59.94p,50p,29.97p,25p,24p,23.98p |
| | 1080/59.94i,50i |
| | 720/59.94p,50p |
| Audio | IN: RCA x 2, OUT: φ3.5 mm TRS |
| AUX | 2 |
| Genlock | BB or Tri-level (Input/through output) |
| USB | USB-Type A x 1 (USB Memory) |
| Power Consumption | 45 W (TBD) |
| Frame Synchronizer | All inputs |
| CC/UC/DC | i/P converter, |
| | DC/UC (1080-720P), CC |
| Keyer | 2 (PinP, Linear key, |
| | Luminance key, Chroma key) |
| USB Video Class Output | USB Type-C, 1ch |
| PTZ Link | Switcher Link, TSL5.0 |
| VMEM | Still x 2 |

| | |
|---|--|
| Shot MEM | Max. 12 presets |
| Dimensions (W x H x D) (excluding protrusions) | 254 mm x 175 mm x 67 mm (10 inches x 6-7/8 inches x 2-5/8 inches) |
| | 1080/59.94p,50p,29.97p,25p,24p,23.98p |
| | 720/59.94p,50p |
| | 1920 x 1080p, 1280 x 720p |
