



Conveniently Compact Switcher Achieves High-quality Video

AV-HSW10

IP Live Switcher with intuitive and compact design takes online communication one level higher.

Key Features

Diverse Interfaces to Suit Wide-ranging Needs

Diverse Keyers for More Attractive Video

Multiviewer With 10 Selectable Patterns

Remote Control With Software Control Panel



AV-HSW10

<https://oc.connect.panasonic.com/nz/en/products/broadcast-proav/av-hsw10>

Video Input	3G-SDI Baseband mode: 4 or 3 IP mode: 1 HDMI Baseband mode: 1 or 2 IP mode: 1 NDI(R)*1*2/Streaming Baseband mode: 2 IP mode: 3
Video Output	3G-SDI Baseband mode: 2 IP mode: 2 HDMI Baseband mode: 1 IP mode: 2 NDI(R)*1*2/Streaming Baseband mode: 2 IP mode: 2
Video Format	
3G-SDI	1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 1080/59.94i, 50i 720/59.94p, 50p
Audio	IN: RCA x 2, OUT: ϕ 3.5 mm TRS
AUX	2
Genlock	BB or Tri-level (Input/through output)
USB	USB-Type A x 1 (USB Memory)
Power Consumption	45 W (TBD)
Frame Synchronizer	All inputs
CC/UC/DC	i/P converter, DC/UC (1080-720P), CC
Keyer	2 (PinP, Linear key, Luminance key, Chroma key)
USB Video Class Output	USB Type-C, 1 ch
PTZ Link	Switcher Link, TSL5.0
VMEM	Still x 2
Shot MEM	Max. 12 presets
Dimensions (W x H x D) (excluding protrusions)	254 mm x 175 mm x 67 mm (10 inches x 6-7/8 inches x 2-5/8 inches)
NDI(R)*1*2	1080/59.94p, 50p, 29.97p, 25p, 24p, 23.98p 720/59.94p, 50p
NDI(R) HX*1*2	1920 x 1080p, 1280 x 720p