



Windows 11 Pro Fully Rugged 2-in-1 Detachable Laptop & Tablet with 12.0" Outdoor Display

TOUGHBOOK 33 mk3 (AU & NZ spec only)

The TOUGHBOOK 33 2-in-1 Detachable Notebook is highly configurable, bringing unrivalled flexibility and performance for mobile business computing professionals. Thanks to the detachable keyboard design and 6 usage modes, the TOUGHBOOK 33 offers the best of all worlds for mobile workers. Target industries for the device include field service workers, maintenance and service technicians in utilities and telecommunications, as well as government agencies, defence, the police and other emergency services.

Key Features

Intel® Core™ i5-1245U vPro™ Processor (optional Intel® Core™ i7 vPro™*)

Windows 11 Pro

12.0" Active Matrix (TFT) colour LCD 2160 x 1440 (QHD) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to 1200cd/m²), IP55 Digitiser

IP65 water and dust resistant, MIL-STD 810H certified***

Long battery life of up to 7 hours with hot swap functionality (up to 14.5 hours with optional large batteries) MobileMark™ 25







TOUGHBOOK 33 mk3 (AU & NZ spec only)

https://oc.connect.panasonic.com/nz /en/products/toughbook/toughbook-33

Mobile Computing Platform	Intel® Core™ i5-1245U vPro™ Processor (optional Intel® Core™ i7 vPro™*)
Operating System	Windows 11 Pro
RAM	Built-in 16GB RAM (optional built-in 32GB RAM*)
iraphic Chip	Intel® UHD Graphics
torage	512GB OPAL NVMe SSD with heater (optional 1TB OPAL NVMe SSD*)
.CD	12.0" Active Matrix (TFT) colour LCD 2160 x 1440 (QHD) LCD with sunlight-viewable glove
	enabled capacitive touchscreen (up to 1200cd/m²), IP55 Digitiser
Bluetooth™	Version 5.1 Class 1
Vireless LAN	Intel® WI-Fi 6 AX201 (up to 2.4 Gbps)
lobile Broadband*	4G LTE
iPS*	U-Blox NEO-M8
AN	x2 (Tablet + Keyboard)
ound	WAVE and MIDI playback, Intel® High Definition Audio subsystem support
ecurity	TPM (TCG V2.0 compliant) Password security (supervisor password, user password, hard disc lock) Integrated hardware security lock slot
ront Camera	2 MP
Rear Camera	8MP with Autofocus and LED flash
D/SDXC Memory Card	x1 Keyboard (optional Micro SD in Tablet*)
Configuration port (Tablet)**	Serial, 2D Barcode Reader, 2nd USB 2.0, Micro SD
JSB 3.1	x3 (x1 Tablet, x2 Keyboard)
JSB 3.1 type C PD	x1 Thunderbolt 4: 40 Gbps (Tablet)
JSB 2.0	x1 optional (Tablet)**
IDNAT	x1 (Keyboard)
IDMI	x2 (Keyboard + Tablet)
/GA	x1 (Keyboard)
Native Serial Port	x1 optional (Tablet)**
	x1 (Keyboard)
Headset	x1 (Tablet)
OC In	x2 (Tablet + Keyboard)
ort Replicator	x1 (Keyboard)
•	x1 (Keyboard) Yes (Tablet + Keyboard)*
Dual Antenna Connector	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader
Oual Antenna Connector Business Expansion Module**	Yes (Tablet + Keyboard)*
Dual Antenna Connector Business Expansion Module** AC Adapter	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader
Oual Antenna Connector Business Expansion Module** AC Adapter	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A
Oual Antenna Connector Business Expansion Module** AC Adapter Battery	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh)
Oual Antenna Connector Business Expansion Module** AC Adapter Battery	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh)
Oual Antenna Connector Business Expansion Module** AC Adapter Battery	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh)
Oual Antenna Connector Business Expansion Module** AC Adapter Battery	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base)
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD)	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD)	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD)	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm
Oual Antenna Connector Business Expansion Module** C Adapter Battery Battery Life Cower Management Dimensions (WxHxD)	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD)	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) Mobile Mark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm Tablet only: 308.0mm x 243.6mm x 21.6mm Tablet + Keyboard: 2.81kg (with standard battery)
Oual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD) Weight	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm Tablet only: 308.0mm x 243.6mm x 21.6mm Tablet only: 1.55kg (with standard battery)
Dual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance Dust Resistance	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm Tablet only: 308.0mm x 243.6mm x 21.6mm Tablet only: 1.55kg (with standard battery) MIL-STD810H, 150cm*** (in Tablet mode) / 150cm (in Clamshell mode)
Dual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance Dust Resistance Water Resistance	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm Tablet only: 308.0mm x 243.6mm x 21.6mm Tablet only: 1.55kg (with standard battery) MIL-STD810H, 150cm*** (in Tablet mode) / 150cm (in Clamshell mode) IP6x
Port Replicator Dual Antenna Connector Business Expansion Module** AC Adapter Battery Battery Life Power Management Dimensions (WxHxD) Weight Drop Resistance Dust Resistance Water Resistance Operating Temperature Standard Configuration	Yes (Tablet + Keyboard)* Smart Card Reader, NFC, Fingerprint Reader Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05A Standard: x2 Li-Ion 11.1V (1,990 mAh) Large* (optional): x2 Li-ion 10.8V (4,120 mAh) Standard: Approx 7 hours (Tablet only) / 6.5 hours (with Keyboard Base) MobileMark™ 25 Large* (optional): Approx 14.5 hours (Tablet only) / 14 hours (with Keyboard Base) MobileMark™ 25 Hot swap, Standby function, ACPI BIOS Tablet + Keyboard: 313.0mm x 288.4mm x 46.1mm Tablet only: 308.0mm x 243.6mm x 21.6mm Tablet + Keyboard: 2.81kg (with standard battery) MIL-STD810H, 150cm*** (in Tablet mode) / 150cm (in Clamshell mode) IP6x IPx5

Footnote * Optional

** One option exlusive possible in configuration port / business expansion module

*** Tested by an independent third party lab following MIL-STD810H Method 516.8 Procedure IV for transit drop test and Method 501.7 and 502.7 Procedure II for operation temperature test. May differ depending on models and options.